

Digital Clamp Meter

CM-2056

HTCTM
INSTRUMENTS

Features :

- Clamp opens 52mm
- Large LCD Display
- **Full function protection**, strong Anti-Interferential Performance.
- Data Hold
- Clamp Light and Backlight display



Technical Data :

Basic Functions	Range	Basic Accuracy
DC Voltage (DCV)	400mV ~ 1000V	±(0.5% + 5digit)
AC Voltage (ACV)	400mV ~ 750V	±(1.0% + 5digit)
DC Current (DCA)	400A/1000A	±(2.0% + 5digit)
AC Current (ACA)	400A/1000A	±(2.0% + 5digit)
Resistance (Ω)	400Ω ~ 40MΩ	±(0.8% + 3digit)
Capacitance(F)	40nF~100uF	±(3.5% + 5digit)
Frequency (Hz)	10Hz~10MHz	±(0.5% + 5digit)
Temperature(°C)	-40~1000 °C	±(1.0% + 5digit)

Special Function :

Diode test	✓	Data Hold	✓
Continuity Testing	Less than 30Ω±10Ω	AC Frequency Response	Current 50-60Hz / Voltage 50-400Hz

- **Standard Accessories** : Test Leads, battery, Manual
- **Dimension** : 270(H) x 123(W) x 50(D)mm