

# AC Clamp Meter

## CM-2100/ CM-2200

**HTC**<sup>TM</sup>  
**INSTRUMENTS**

### Features :

- 3 ¾ Digits Display
- 4000 Counts
- CE CAT III 600V
- Data Hold Function
- Auto Range or Manual Range Selection
- Max. Jaw Size : 57mm
- AC Current 1500A(CM-2100)
- AC Current 1500A(CM-2200)
- Auto Power Off



### Technical Data :

Function	Range	Resolution	Accuracy	Input Impedance
DCV	4/40/400/1000V	1mV	±(1.0% +3d)	10MΩ
ACV	4/40/400/750V	1mV	±(1.5% +5d)	10MΩ
ACA	400/1500A(CM-2100) 400/2000A(CM-2200)	0.1A	±(2.5% +5d)	
Resistance	400/4k/40k/400k/ 4M/40MΩ	0.1Ω	±(1.0% +3d)	
Frequency	10/100/1K/10k/ 100k/1MHz	0.01Hz	±(1.0% +3d)	
Continuity	Buzzer Sound at less than 20Ω			
Diode		1mV		

- **Standard Accessories** : Carrying case, Test Leads ,Manual
- **Dimension** : 280(H) x 100(W) x 50(D)mm