

Sound Level Meter

SL-1352

HTCTM
INSTRUMENTS

Features:

- Max & Min Measurement
- Over Range Display
- Under range display
- A & C Weighting
- FAST & SLOW response
- Analog AC/DC Outputs for connection to frequency analyzer or X-Y shaft recorder
- Datalogger function
- Adjustable Alarm Levels
- Backlight
- **USB Computer Interface** (advanced Software program for all Windows)

Technical Data:

Basic Function	Range
Accuracy	1.4dB
Resolution	0.1dB
Frequency Range	31.5Hz ~8kHz
Dynamic Range	50dB
Level Range	Low:30dB~80dB Medium:50dB~100dB High:80dB~130dB Auto: 30dB~130dB
Time Wiegthing	FAST (125mS),SLOW (1s)
Microphone	½ inch electric condenser microphone
Display Update	2 times/sec
Analog Output	AC/DC outputs,AC= 1Vrms,DC= 10mV/dB

Special Function:

Alarm	Electron	Power Supply	1 x9VBattery
--------------	----------	---------------------	--------------

- **Standard Accessories** : Gift Box with Hard Carrying Case, Manual , Battery,



Screwdriver, Audio Plug, Windscreen,
Tripod & DC 9V power supply,
HTC USB with Software

- **Dimension** : 278(H) x 76(W) x 50(D)mm